

<b>NITRILE</b>	<b>BLACK</b>	<b>POWDER FREE</b>	<b>S-XL</b>	<b>AMBIDEXTROUS</b>	<b>NON STERIL</b>
----------------	--------------	--------------------	-------------	---------------------	-------------------

Comfortable glove. Offers protection against specific chemical hazards and solvents in sporadic contact. Frequently used in catering and food industry, laboratories, medical and paramedical practices, cleaning and hygiene and DIY.

### Characteristics

<b>Suitable for latex allergic people.</b>	<b>Finger textured. Making easy grip.</b>
<b>Powder free, single use, ambidextrous</b>	<b>High durability and resistance.</b>
<b>Rolled Edge, protection against spills.</b>	<b>Flexibility and adaptability.</b>

### Packaging

- 100 pieces per dispenser, with a pre-punched opening for hygienic access to the gloves.
- Packaging contains: 10 dispensers of 100 units
- Dimension: 210 x 120 x 70 mm



**Labelling** Manufacturing date, expiration date, batch number, reference and EAN code. Product name in several languages: Spanish, English, French, German, Italian, Portuguese.

CE marking, protection pictograms, safety standards and legislation. Size, size guide and units.



## Standards:

- CE marking PPE Category III according to Regulation (EU) 2016/425
- CE marking MDD Class I according to Regulation (EU) 2017/745
- Complies with food handling requirements of Regulation (EU) 10/2011
- ISO 16604:2004: Bacteriophage
- EN ISO 374-1:2016/A1:2018. Point 7 EN 374-2. Point 5 EN 374-4
- EN ISO 374-5:2016
- EN 420:2003+A1:2009
- EN 455-1-2-3-4

## Chemical resistance:

### PERMEATION (EN ISO 374-1:2016/A1.2018, type B)

Gloves are classified in terms of time of passage, according to each individual chemical for which the glove resists permeation:

CHEMICALS	LEVEL	LETTER
N-HEPTANE	6	J
SODIUM HYDROXIDE 40%	6	K
FORMALDEHYDE 37%	2	T

## Performance Level:

Time (min)	> 10	> 30	> 60	> 120	> 240	> 480
Performance Level	1	2	3	4	5	6

## DEGRADATION

Degradation % (DR) is determined for each chemical used in the permeation tests.

(DR) J: n-Heptane= 52.01%

(DR) K: Sodium Hydroxide 40% = -50.99%

(DR) T: Formaldehyde 37% = 14.16%



The “Gentle Touch Nitrile”, nitrile glove PPE should be used to protect the user’s hand against chemical risks (products and levels mentioned above) and against microbiological risks (bacteria, fungi and virus).

The present PPE should never be used against other risks than those described above. The use of his PPE should be evaluated correctly depending on the place of work.


EN ISO 374-1:2016/A1:2018

EN ISO 374-5:2016



GLOVE SIZES		S	M	L	XL
Palm width	±5 mm	86	96	107	115
Length	mm	240	240	240	240
Palm thickness	±0,02 mm	0.115	0.115	0.115	0.115
Finger thickness	±0,02 mm	0.13	0.13	0.13	0.13
Cuff thickness	± 0,02 mm	0.08	0.08	0.08	0.08
Weight	± 0,3 g	4.8	5.0	5.3	5.5





Made in Malaysia by Rubberex

Distributed by Exive International

Rubberex Alliance SDNB. BHD  
Lot 138201 Off ¼ Mile,  
Jalan Bercham  
Kawasan Perindustrian Bercham,  
Malaysia

Phone: +31 316 343748  
Email: [sales@exive.eu](mailto:sales@exive.eu)  
Kelvinstraat 12  
6902 PW Zevenaar  
The Netherlands

